## NSN 5935-01-369-8328

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-369-8328

Body Style:
Right angle type
Overall Length:
5.000 inches
Overall Width:
0.385 inches
Body Height:
0.330 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
3 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Friction
Operating Tempurature Rating:
Between -65.0 degrees celsius and 105.0 degrees celsius
Unable To Decode:
Unable to decode and unable to decode
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping
Terminal Type:
Printed circuit single mating end single contact grouping
Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:

**Included Contact Type:** 

Square pin single mating end single contact grouping

135 single mating end single contact grouping

## NSN 5935-01-369-8328

Electrical Receptacle Connector - Page 2 of 2



## **Special Features:** Jackscrew type-male and location-right handandjackscrew type-male and location-left hand **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.135 gold grains, troy **Precious Material:** Gold **Supplementary Features:** Mounting method - welded and surface Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A039b0

Mil-std (military Standard):

Mil-g-45204 spec.