NSN 5935-01-370-0912

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-370-0912 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.167 inches **Overall Height:** 1.258 inches **Overall Width:** 1.258 inches **Unthreaded Mounting Hole Diameter:** 0.126 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.974 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.974 inches **Distance From Mounting Shoulder To Front Face:** Between 0.765 inches and 0.775 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 16-07 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0 and 105.0 and 140.0 and 215.0 and 265.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin Thready Qty Per Inch (tpi): 28 **Thread Size:** 1.000 inches

Terminal Location:

Back single mating end single contact grouping

NSN 5935-01-370-0912

Electrical Receptacle Connector - Page 2 of 2



Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic epoxy single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Nickel
Included Contact Quantity:
7 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.007 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-81511 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Un
Specification Data:
81349-mil-c-81511/51 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0