

View Online at <https://aerobasegroup.com/nsn/5935-01-370-1178>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

0.765 inches

Bushing Diameter:

0.250 inches

Overall Height:

0.510 inches

Overall Width:

0.510 inches

Environmental Protection:

Corrosion resistant

Unthreaded Mounting Hole Diameter:

0.102 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.340 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.340 inches

Distance From Mounting Shoulder To Front Face:

0.365 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Sma single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

18.0 gigahertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thread Length:

0.170 inches

Operating Temperature Rating:

Between -65.0 degrees celsius and 105.0 degrees celsius

Thready Qty Per Inch (tpi):

36

Thread Size:

0.250 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic single mating end

Contact Surface Treatment Specification:

Mil-g-45204, ty2, cl 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Tab, solder lug single mating end single contact grouping

Shell Material:

Stainless steel

Shell Surface Treatment:

Passivate

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.