NSN 5935-01-370-1844



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-370-1844 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.913 inches **Overall Height:** 1.812 inches **Overall Width:** 1.812 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.500 inches **Distance From Mounting Shoulder To Front Face:** 0.674 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 25-29 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0 and 164.0 and 218.0 and 280.0 Shell Type: **Connector Locking Method:** Externally threaded shell **Thread Size:** 1.625 inches

Terminal Location: Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping

NSN 5935-01-370-1844

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Glass single mating end
Terminal Type:
Wire loop single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Passivate
Included Contact Quantity:
29 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.029 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Specification Data:
81349-mil-c-38999/21 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0