Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-370-3487

**Body Style:** Right angle, type **Overall Length:** 5.300 inches **Overall Height:** 0.380 inches **Body Width:** 0.330 inches **Unthreaded Mounting Hole Diameter:** 0.130 inches **Distance Between Mounting Facility Centers:** 5.030 inches Mating End Quantity: 1 **Contact Position Arrangement Style:** 3 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1200.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 2500.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket **Connector Locking Method:** Friction **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Printed circuit single mating end single contact grouping Unable To Decode: Unable to decode and unable to decode **Included Contact Quantity:** 

47 single mating end single contact grouping



Included Contact Type:

Round pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.047 gold grains, troy

Precious Material:

Gold

## Supplementary Features:

Mounting method - unthreaded hole

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0