NSN 5935-01-370-7056

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-370-7056

Body Style:
Straight shape
Overall Length:
5.750 inches
Overall Height:
0.450 inches
Overall Width:
0.490 inches
Environmental Protection:
Shock resistant and vibration resistant and corrosion resistant and fungus resistant
Unthreaded Mounting Hole Diameter:
0.098 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
3 rows of contacts non-inserted board single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Mating end
Connector Locking Method:
Connector Locking Method: Friction
-
Friction
Friction Operating Tempurature Rating:
Friction Operating Tempurature Rating: Between -65.0 degrees celsius and 125.0 degrees celsius
Friction Operating Tempurature Rating: Between -65.0 degrees celsius and 125.0 degrees celsius Terminal Location:
Friction Operating Tempurature Rating: Between -65.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping
Friction Operating Tempurature Rating: Between -65.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material:
Friction Operating Tempurature Rating: Between -65.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Friction Operating Tempurature Rating: Between -65.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:
Friction Operating Tempurature Rating: Between -65.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping
Friction Operating Tempurature Rating: Between -65.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material:
Friction Operating Tempurature Rating: Between -65.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic diallyl phthalate glass filled single mating end
Friction Operating Tempurature Rating: Between -65.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic diallyl phthalate glass filled single mating end Contact Surface Treatment Specification:
Friction Operating Tempurature Rating: Between -65.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic diallyl phthalate glass filled single mating end Contact Surface Treatment Specification: Mil-g-45204 military specification 1st treatment response single mating end single contact grouping
Friction Operating Tempurature Rating: Between -65.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic diallyl phthalate glass filled single mating end Contact Surface Treatment Specification: Mil-g-45204 military specification 1st treatment response single mating end single contact grouping Terminal Type:
Friction Operating Tempurature Rating: Between -65.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic diallyl phthalate glass filled single mating end Contact Surface Treatment Specification: Mil-g-45204 military specification 1st treatment response single mating end single contact grouping Terminal Type: Printed circuit single mating end single contact grouping

Round socket single mating end single contact grouping

NSN 5935-01-370-7056

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.150 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-55302/130 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
8134955302/130-29 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.