Electrical Plug Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-01-371-5290



# Thread Class:

2b

**Thread Direction:** 

Right-hand

## Body Style:

Straight shape, internal coupling

### **Overall Length:**

33.16 millimeters

#### **Overall Diameter:**

35.7 millimeters

#### Threaded Device Type:

Back shell and coupling facility

## Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

17-8 single mating end

## **Contact Removability:**

Removable single mating end single contact grouping

## **Polarization Method:**

Key, multiple key groove

## **Insert Position In Deg:**

 $0.0 \mbox{ and } 49.0 \mbox{ and } 169.0 \mbox{ and } 200.0 \mbox{ and } 244.0$ 

## Shell Type:

Solid

# **Connector Locking Method:**

Internally threaded coupling ring

# Thread Size:

25.0 millimeters and 1.188 inches

# **Terminal Location:**

Back single mating end single contact grouping

# Contact Material:

Copper alloy single mating end single contact grouping

# Contact Surface Treatment:

Gold single mating end single contact grouping

# Insert Material:

Plastic epoxy single mating end

# Terminal Type:

Crimp single mating end single contact grouping

# Shell Material:

Aluminum alloy

# Shell Surface Treatment:

Passivate

# NSN 5935-01-371-5290

Electrical Plug Connector - Page 2 of 2



**Thread Tolerance Class:** 

6h external

**Included Contact Quantity:** 

8 single mating end single contact grouping

## Included Contact Type:

Round socket single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:** 

0.008 gold grains, troy

#### **Precious Material:**

Gold

#### Test Data Document:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Thread Series Designator:**

Iso m and special acme

#### **Specification Data:**

81349-mil-c-38999/26 government specification

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

#### Fiig:

A039b0