NSN 5935-01-371-5293

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-371-5293 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, external/internal coupling **Overall Length:** 1.359 inches **Overall Diameter:** 0.562 inches **Environmental Protection:** Vibration resistant and corrosion resistant and moisture resistant and shock resistant **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Bnc 1st mating endsma 2nd mating end **Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Ac Voltage Rating In Volts:** 335.0 single mating end all contact groupings Shell Type: Solid **Connector Locking Method:** Bayonet pin and internally threaded coupling nut Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end all contact groupings Thready Qty Per Inch (tpi): 36 **Thread Size:** 0.250 inches **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Gold single mating end all contact groupings **Criticality Code Justification:** Feat **Shell Material:** Steel **Included Contact Quantity:**

moraded Comact Quantity

1 single mating end 1st contact grouping1 single mating end 2nd contact grouping

NSN 5935-01-371-5293

Connector Adapter - Page 2 of 2

Fiig: A039b0



Included Contact Type:
Coaxial socket single mating end 1st contact groupingcoaxial pin single mating end 2nd contact grouping
Special Features:
Without safety wire hole
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.010 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-55339 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specificatio
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Uns
Specification Data:
81349-mil-c-55339/47 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No