

View Online at <https://aerobasegroup.com/nsn/5935-01-371-5307>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.500 inches

Overall Diameter:

0.312 inches

Environmental Protection:

Corrosion resistant and vibration resistant and moisture resistant and thermal shock resistant

Cable Entrance Diameter:

0.079 inches

Distance From Mounting Shoulder To Front Face:

0.450 inches

Mounting Facility Thickness:

0.125 inches

Threaded Device Type:

Coupling facility and mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

Sma single mating end

Contact Removability:

Removable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Connector Cable Strain Relief Method:

Compression nut and shrinkable tubing

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thready Qty Per Inch (tpi):

36

Thread Size:

0.250 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic fluorinated ethylene propylene single mating end or plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-452-4, type 2, cl 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Copper alloy

Shell Material Specification:

Astm b196 federal specification single material response

Insert Material Specification:

L-p-389 federal specification single material response single mating end or l-p-403 federal specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-452-4 spec.