## NSN 5935-01-372-0913

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-372-0913 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 1.110 inches **Overall Height:** 1.640 inches **Overall Width:** 0.380 inches **Distance Between Mounting Facility Centers:** 0.906 inches **Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Jackscrew **Connector Locking Method:** Jackscrew-socket **Thread Size:** 0.138 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate mineral filled single mating end

**Terminal Type:** 

Solder well single mating end single contact grouping

**Unable To Decode:** 

Unable to decode and unable to decode

## NSN 5935-01-372-0913

Fiig: A039b0

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
7 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Jackscrew type-female and location-left handandjackscrew type-male and location-right hand
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.007 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
<b></b>
Demilitarization:
No