# NSN 5935-01-372-1978

Thread Class: 2b and 2a

**Thread Direction:** 

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-372-1978

Right-hand			
Body Style:			
Straight shape, internal coupling			
Overall Length:			
1.180 inches			
Overall Diameter:			
1.236 inches			
Threaded Device Type:			
Coupling facility and back shell			
Mating End Quantity:			
1			
Contact Position Arrangement Style:			
"14-4, 14-04" single mating end			
Contact Removability:			
Removable single mating end single contact grouping			
Polarization Method:			
Key, multiple key groove			
Insert Position In Deg:			
0.0 and 18.0 and 149.0 and 192.0 and 259.0			
Shell Type:			
Solid			
Connector Locking Method:			
Internally threaded coupling ring			
Thread Size:			
0.938 inches and 0.875 inches			
Terminal Location:			
Back single mating end single contact grouping			
Contact Material:			
Copper alloy single mating end single contact grouping			
Insert Material:			
Plastic epoxy single mating end			
Terminal Type:			
Crimp single mating end single contact grouping			
Shell Material:			
Stainless steel			
Shell Surface Treatment:			
Passivate			
Included Contact Quantity:			
4 single mating end single contact grouping			

## NSN 5935-01-372-1978

Electrical Plug Connector - Page 2 of 2



### **Included Contact Type:**

Round socket single mating end single contact grouping

### **Test Data Document:**

81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

<b>Thread</b>	<b>Series</b>	Design	ator:

Unef

### **Specification Data:**

81349-mil-c-83723/95 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0