

View Online at <https://aerobasegroup.com/nsn/5935-01-372-5359>

Body Style:

Straight shape, internal coupling

Overall Length:

1.230 inches

Overall Diameter:

0.570 inches

Environmental Protection:

Moisture resistant and fungus proof and salt water resistant and shock resistant and vibration proof

Cable Entrance Diameter:

Between 0.313 inches and 0.333 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Frequency Rating:

500.0 megahertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet slot

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Copper single mating end single contact grouping and nickel single mating end single contact grouping and gold single mating end single contact grouping

Insert Material:

Plastic polychlorotrifluoroethylene single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Nickel

Included Contact Quantity:

2 single mating end single contact grouping

Included Contact Type:

Triaxial pin single mating end single contact grouping

Special Features:

Cable type g503456-1

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.002 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0