Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-372-6789

| Body Style: |
|--|
| Wall type |
| Overall Height: |
| 1.187 inches |
| Overall Width: |
| 1.625 inches |
| Body Length: |
| 1.937 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.138 inches |
| Distance Between Mounting Facility Centers: |
| 3.281 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| "3, 5-15" single mating end |
| Contact Removability: |
| Nonremovable single mating end all contact groupings |
| Contact Maximum Current Rating In Amps: |
| 20.0 single mating end all contact groupings |
| Contact Maximum Ac Voltage Rating In Volts: |
| 125.0 single mating end all contact groupings |
| Polarization Method: |
| Contact |
| Connector Locking Method: |
| Friction |
| Terminal Location: |
| Side single mating end all contact groupings |
| Contact Material: |
| Copper alloy single mating end all contact groupings |
| Insert Material: |
| Plastic polyamide single mating end |
| Terminal Type: |
| Screw single mating end all contact groupings |
| Included Contact Quantity: |
| 2 single mating end 2nd contact grouping |
| Included Contact Type: |
| Flat socket single mating end 2nd contact grouping |
| Color: |
| Brown |
| Shelf Life: |
| N/a |
| ι w/ α |

Electrical Receptacle Connector - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0