

View Online at <https://aerobasegroup.com/nsn/5935-01-372-9529>

Body Style:

Pcb, external coupling

Overall Length:

0.386 inches

Overall Height:

0.375 inches

Overall Width:

0.375 inches

Environmental Protection:

Chemical resistant and cold resistant and corrosion resistant and fungus resistant and moisture resistant and shock resistant and vibration resistant

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.200 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.200 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Smb single mating end

Contact Maximum Frequency Rating:

4.0 gigahertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Snap lock

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Operating Temperature Rating:

Between -65.0 degrees celsius and 165.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Insert Material:

Plastic polychlorotrifluoroethylene single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Gold

Shell Surface Treatment Specification:

Mil-g-45204, type 2, class 1 military specification single treatment response

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Body surface gold

Precious Material And Weight:

0.500 gold grains, troy

Precious Material:

Gold

Supplementary Features:

Mounting method - stud

Test Data Document:

81349-mil-c-39012/95 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349--39012/95-0006 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.