NSN 5935-01-373-0432

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-373-0432 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 1.938 inches **Overall Diameter:** 1.141 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 13-12 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0 and 90.0 and 145.0 and 195.0 and 252.0 Shell Type: Solid **Connector Locking Method:** Internally threaded coupling ring Thready Qty Per Inch (tpi): 20 and 10 Thread Size: 0.875 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic fluorosilicone single mating end **Criticality Code Justification:** Feat

Terminal Type:

Crimp single mating end single contact grouping

NSN 5935-01-373-0432Electrical Plug Connector - Page 2 of 2



Shell Material:
Aluminum
Shell Surface Treatment:
Cadmium and chromate and nickel
Included Contact Quantity:
12 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
No. 20 pin with crimp for 20 gauge
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.012 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-28840 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef and double stub
Specification Data:
81349-mil-c-28840 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A039b0