## NSN 5935-01-373-3058

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-373-3058

Body Style:
Straight type
Overall Length:
2.150 inches
Overall Height:
0.465 inches
Overall Width:
0.250 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
1.900 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Friction
Features Provided:
Low insertion force contact
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping or gold single mating end single contact
grouping and copper single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end
Criticality Code Justification:
Feat
Terminal Type:
Solder well single mating end single contact grouping

**Included Contact Quantity:** 

**Guide Design And Location:** 

26 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

D shape socket left-hand at 9 oclock and d shape pin right-hand at 9 oclock

## NSN 5935-01-373-3058

A039b0

Electrical Receptacle Connector - Page 2 of 2



Special Features:
Item supplied without loctite and be reset in required positions.
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.026 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-55302/58 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig: