NSN 5935-01-373-3059

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-373-3059 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.630 inches **Overall Diameter:** 0.320 inches **Distance From Mounting Shoulder To Front Face:** Between 0.400 inches and 0.440 inches **Mounting Facility Thickness:** Between 0.023 inches and 0.096 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Smb single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Friction **Thread Size:** 0.190 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic fluorinated ethylene propylene single mating end or plastic polytetrafluoroethylene single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Copper

Silver and copper

Shell Surface Treatment:

NSN 5935-01-373-3059

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/flat
Included Contact Type:
Coaxial pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and shell surface silver
Precious Material And Weight:
0.005 gold grains, troy and 0.100 silver grains, troy
Precious Material:
Gold and silver
Test Data Document:
81349-mil-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unf
Specification Data:
81349-mil-c-39012 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-39012 spec.