NSN 5935-01-373-9789

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-373-9789

Body Style:

Angle shape, pcb type

Overall Length:

5.650 inches

Overall Height:

0.550 inches

Overall Width:

0.359 inches

Environmental Protection:

Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant

Unthreaded Mounting Hole Diameter:

0.120 inches

Distance Between Mounting Facility Centers:

5.900 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204. type 2, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty sdg-f or ty gdi-30f military specification 1st material response single mating end or mil-m-24519, ty gpt-30f or gst-40f military specification 2nd material response single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

90 single mating end single contact grouping

NSN 5935-01-373-9789

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type: Round pin single mating end single contact grouping Precious Material And Location: Contact surfaces gold Precious Material And Weight: 0.090 gold grains, troy Precious Material: Gold Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.