

View Online at <https://aerobasegroup.com/nsn/5935-01-374-0654>

Body Style:

Rectangular shape, angle

Overall Length:

2.088 inches

Overall Height:

0.494 inches

Overall Width:

1.113 inches

Unthreaded Mounting Hole Diameter:

0.125 inches

Distance Between Mounting Facility Centers:

1.852 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

"b, 17w2" single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

5.0 single mating end 1st contact grouping30.0 single mating end 2nd contact grouping

Shell Type:

Solid

Connector Locking Method:

Jackscrew and friction

End Application:

NSN4-92-001-3399

Operating Temperature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Unable To Decode:

Unable to decode and unable to decode

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

Insert Material:

Plastic polyester glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end all contact groupings

Terminal Type:

Printed circuit single mating end all contact groupings

Shell Material:

Steel

Shell Surface Treatment:

Cadmium and dichromate

Insert Material Specification:

Mil-m-24519 military specification single material response single mating end

Included Contact Quantity:

2 single mating end 1st contact grouping15 single mating end 2nd contact grouping

Included Contact Type:

Coaxial socket single mating end 1st contact groupinground socket single mating end 2nd contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.025 gold grains, troy

Precious Material:

Gold

Supplementary Features:

Mounting method - terminal and unthreaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.