NSN 5935-01-374-2905

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-374-2905 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.430 inches **Overall Height:** 1.437 inches **Overall Width:** 1.437 inches **Unthreaded Mounting Hole Diameter:** Between 0.116 inches and 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.156 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.156 inches **Distance From Mounting Shoulder To Front Face:** Between 0.708 inches and 0.728 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 20-28 single mating end **Contact Removability:** Removable single mating end all contact groupings **Polarization Method:** Key, multiple key groove **Insert Position In Deg:**

0.0 and 105.0 and 140.0 and 215.0 and 265.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thread Size:

1.188 inches and 1.312 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

NSN 5935-01-374-2905

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Gold single mating end all contact groupings
Insert Material:
Plastic epoxy single mating end
Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
4 single mating end 1st contact grouping24 single mating end 2nd contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.044 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Specification Data:
81349-mil-c-83723/83 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0