# NSN 5935-01-374-2906

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-374-2906 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.430 inches **Overall Height:** 1.437 inches **Overall Width:** 1.437 inches **Environmental Protection:** Humidity resistant **Unthreaded Mounting Hole Diameter:** Between 0.116 inches and 0.125 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.156 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.156 inches **Distance From Mounting Shoulder To Front Face:** Between 0.708 inches and 0.728 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 20-28 single mating end **Contact Removability:** Removable single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 101.0 and 168.0 and 211.0 and 342.0 **Shell Type:** Solid **Connector Locking Method:** Externally threaded shell

**Thread Size:** 

1.188 inches and 1.312 inches

**Terminal Location:** 

Back single mating end all contact groupings

# NSN 5935-01-374-2906

Electrical Receptacle Connector - Page 2 of 2



_							
-	∩n	+-	~+	N/I	210	ria	

Copper alloy single mating end all contact groupings

#### **Contact Surface Treatment:**

Gold single mating end all contact groupings

### **Insert Material:**

Plastic epoxy single mating end

### **Contact Surface Treatment Specification:**

Mil-g-45204, type 1, cl 2 military specification single treatment response single mating end all contact groupings

### **Terminal Type:**

Crimp single mating end all contact groupings

### **Shell Material:**

Aluminum alloy

#### **Shell Surface Treatment:**

Cadmium

### **Shell Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response

### **Shell Material Specification:**

Qq-a-367 federal specification single material response

### **Included Contact Quantity:**

4 single mating end 1st contact grouping24 single mating end 2nd contact grouping

### **Included Contact Type:**

Round pin single mating end all contact groupings

### **Precious Material And Location:**

Contact surfaces gold

### **Precious Material And Weight:**

0.028 gold grains, troy

### **Precious Material:**

Gold

### **Test Data Document:**

81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Thread Series Designator:**

Unef

### **Specification Data:**

81349-mil-c-83723/83 government specification

#### Shelf Life:

N/a

### **Unit Of Measure:**

--

### Demilitarization:

No

## Fiig:

A039b0

### Mil-std (military Standard):

•