Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-374-2916

| Thread Class: |
|---|
| 2a |
| Za Thread Direction: |
| |
| Right-hand |
| Body Style: |
| Straight shape, external coupling Overall Length: |
| 1.098 inches |
| Overall Height: |
| 0.937 inches |
| Overall Width: |
| 0.937 inches |
| |
| Unthreaded Mounting Hole Diameter: Between 0.116 inches and 0.125 inches |
| |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| 0.719 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 0.719 inches |
| Distance From Mounting Shoulder To Front Face: |
| Between 0.708 inches and 0.728 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 5-oct single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Externally threaded shell |
| Thread Size: |
| 0.688 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Terminal Type: |
| Solder well single mating end single contact grouping |

NSN 5935-01-374-2916

Electrical Receptacle Connector - Page 2 of 2



| Shell Material: |
|--|
| Aluminum alloy |
| Included Contact Quantity: |
| 5 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.025 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unef |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Domilitarization: |

Demilitarization:

No

Fiig:

A039b0