

View Online at <https://aerobasegroup.com/nsn/5935-01-374-8394>

Thread Class:

2a and 2b

Thread Direction:

Right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

1.340 inches

Overall Diameter:

1.625 inches

Environmental Protection:

Humidity resistant and salt water resistant and shock proof and vibration proof

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

22-55 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0 and 84.0 and 152.0 and 204.0 and 334.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

End Application:

C-17a acft

Operating Temperature Rating:

Between -65.0 degrees celsius and 200.0 degrees celsius

Thread Size:

1.3125 inches and 1.4375 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic epoxy single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification 1st treatment response

Shell Material Specification:

Qq-a-367 federal specification single material response

Included Contact Quantity:

55 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Self-locking coupling nut

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.055 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-83723/96 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

81349--83723/96w22558 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.