## NSN 5935-01-374-9298

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-374-9298

Thread Class:
2a and 2b
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
1.060 inches
Overall Height:
0.520 inches
Overall Width:
0.270 inches
Distance Between Mounting Facility Centers:
0.814 inches
Threaded Device Type:
Coupling facility and mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
20 20-20 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Thread Size:
0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate glass filled single mating end
Terminal Type:
Solder well single mating end single contact grouping
Unable To Decode:
Unable to decode and unable to decode

## NSN 5935-01-374-9298

Fiig: A039b0

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
20 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Jackscrew type-male and location-right handandjackscrew type-female and location-left hand
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.020 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No