

View Online at <https://aerobasegroup.com/nsn/5935-01-375-0690>

Body Style:

Straight shape, external/internal coupling

Overall Length:

0.970 inches

Overall Diameter:

0.312 inches

Environmental Protection:

Corrosion resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

Rf all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Contact Maximum Frequency Rating:

38.0 gigahertz all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping

Insert Material:

Plastic polytetrafluoroethylene all mating ends

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response all mating ends single contact grouping

Contact Material Specification:

Qq-c-530, condition h federal specification single material response all mating ends single contact grouping

Shell Material:

Stainless steel

Shell Surface Treatment:

Passivate

Shell Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Shell Material Specification:

Astm a582 assn standard single material response

Insert Material Specification:

Mil-p-19468 military specification single material response all mating ends

Included Contact Quantity:

1 all mating ends single contact grouping

Included Contact Type:

Coaxial socket all mating ends single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.