## NSN 5935-01-375-2917

**Thread Direction:** 

Right-hand **Body Style:** 

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-375-2917 **Thread Class:** 2b

Straight shape, internal coupling **Overall Length:** 33.16 millimeters **Overall Diameter:** 48.0 millimeters **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 25-43 single mating end **Contact Removability:** Removable single mating end all contact groupings **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0 and 79.0 and 153.0 and 197.0 and 272.0 Shell Type: Solid **Connector Locking Method:** Internally threaded coupling ring **Thread Size:** 37.0 millimeters and 1.625 inches **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Gold single mating end all contact groupings **Insert Material:** Plastic epoxy single mating end **Terminal Type:** Crimp single mating end all contact groupings **Shell Material:** Aluminum alloy

**Shell Surface Treatment:** 

Cadmium

## **NSN 5935-01-375-2917**Electrical Plug Connector - Page 2 of 2



Thread Tolerance Class:
6h external
Included Contact Quantity:
20 single mating end 1st contact grouping23 single mating end 2nd contact grouping
Included Contact Type:
Round socket single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.043 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Iso m and special acme
Specification Data:
81349-mil-c-38999/26 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A039b0