NSN 5935-01-375-3476

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-375-3476

Body Style:
Straight shape
Overall Length:
5.800 inches
Overall Height:
0.850 inches
Overall Width:
0.260 inches
Unthreaded Mounting Hole Diameter:
0.094 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
184 single mating end
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
900.0 single mating end single contact grouping
Shell Type:
Solid
Connector Leaking Mathada
Connector Locking Method:
Friction
-
Friction
Friction Operating Tempurature Rating:
Friction Operating Tempurature Rating: Between -55.0 degrees celsius and 200.0 degrees celsius
Friction Operating Tempurature Rating: Between -55.0 degrees celsius and 200.0 degrees celsius Terminal Location:
Friction Operating Tempurature Rating: Between -55.0 degrees celsius and 200.0 degrees celsius Terminal Location: Back single mating end single contact grouping
Friction Operating Tempurature Rating: Between -55.0 degrees celsius and 200.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material:
Friction Operating Tempurature Rating: Between -55.0 degrees celsius and 200.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Friction Operating Tempurature Rating: Between -55.0 degrees celsius and 200.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:
Friction Operating Tempurature Rating: Between -55.0 degrees celsius and 200.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping
Friction Operating Tempurature Rating: Between -55.0 degrees celsius and 200.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material:
Friction Operating Tempurature Rating: Between -55.0 degrees celsius and 200.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Resin synthetic single mating end
Friction Operating Tempurature Rating: Between -55.0 degrees celsius and 200.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Resin synthetic single mating end Terminal Type:
Friction Operating Tempurature Rating: Between -55.0 degrees celsius and 200.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Resin synthetic single mating end Terminal Type: Solder well single mating end single contact grouping
Friction Operating Tempurature Rating: Between -55.0 degrees celsius and 200.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Resin synthetic single mating end Terminal Type: Solder well single mating end single contact grouping Shell Material:
Friction Operating Tempurature Rating: Between -55.0 degrees celsius and 200.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Resin synthetic single mating end Terminal Type: Solder well single mating end single contact grouping Shell Material: Aluminum alloy
Friction Operating Tempurature Rating: Between -55.0 degrees celsius and 200.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Resin synthetic single mating end Terminal Type: Solder well single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment:

Contact surfaces gold

Precious Material And Location:

NSN 5935-01-375-3476

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Weight:
0.184 gold grains, troy
Precious Material:
Gold
Supplementary Features:
Mounting method - unthreaded hole
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0