NSN 5935-01-375-5095

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-375-5095

| Body Style: |
|--|
| Straight shape |
| Overall Length: |
| 6.150 inches |
| Overall Height: |
| 0.465 inches |
| Overall Width: |
| 0.250 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.120 inches |
| Distance Between Mounting Facility Centers: |
| 5.900 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 2 rows of contacts non-inserted board single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 5.0 single mating end single contact grouping |
| Polarization Method: |
| Guide pin/socket |
| Connector Locking Method: |
| Friction |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Plastic polyphenylene single mating end and glass single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Guide Design And Location: |
| D shape socket right-hand at 3 oclock d shape pin left-hand at 12 oclock |
| Included Contact Quantity: |
| 100 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| |

Contact surfaces gold

NSN 5935-01-375-5095

Electrical Receptacle Connector - Page 2 of 2



| Precious | Material | And | Weight: |
|----------|----------|-----|---------|
| | | | |

0.100 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0