NSN 5935-01-375-9201

Electrical Modular Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-375-9201 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Rectangular shape **Overall Length:** 2.010 inches **Overall Height:** 1.676 inches **Overall Width:** 0.410 inches **Environmental Protection:** Corrosion resistant and salt spray proof **Unthreaded Mounting Hole Diameter:** 0.150 inches **Distance Between Mounting Facility Centers:** 1.270 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Polarization plate Shell Type: Solid **Connector Locking Method:** Jackscrew **Thread Size:** 0.138 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping

Insert Material:Plastic single mating end

NSN 5935-01-375-9201

Electrical Modular Receptacle Connector - Page 2 of 2



Criticality Code Justification:
Feat
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Metal
Shell Surface Treatment:
Nickel
Included Contact Quantity:
20 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Polarized at position a
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.020 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0