NSN 5935-01-375-9203

Electrical Modular Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-375-9203 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Rectangular shape **Overall Length:** 2.010 inches **Overall Height:** 1.676 inches **Overall Width:** 0.410 inches **Environmental Protection:** Corrosion resistant and salt spray proof **Unthreaded Mounting Hole Diameter:** 0.150 inches **Distance Between Mounting Facility Centers:** 1.270 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Polarization plate Shell Type: Solid **Connector Locking Method:** Jackscrew **Thread Size:** 0.138 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end 2nd contact grouping

Insert Material:

Plastic single mating end

NSN 5935-01-375-9203

Electrical Modular Receptacle Connector - Page 2 of 2



| Criticality Code Justification: |
|--------------------------------------------------------|
| Feat |
| Terminal Type: |
| Crimp single mating end single contact grouping |
| Shell Material: |
| Metal |
| Shell Surface Treatment: |
| Nickel |
| Included Contact Quantity: |
| 20 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Special Features: |
| Polarized at position c |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.020 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| . - |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |