NSN 5935-01-376-0852

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-376-0852 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.490 inches **Cable Entrance Diameter:** 0.120 inches **Distance From Mounting Shoulder To Front Face:** 0.450 inches **Mounting Facility Thickness:** 0.125 inches **Threaded Device Type:** Coupling facility and mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Sma single mating end **Contact Removability:** Removable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Connector Cable Strain Relief Method:** Shrinkable tubing Width Across Flats: 0.312 inches Thready Qty Per Inch (tpi): **Thread Size:** 0.250 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping

Insert Material:
Rubber fluorocarbon class fpm single mating end

NSN 5935-01-376-0852

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Stainless steel
Shell Surface Treatment:
Gold or passivate
Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact and shell surfaces gold
Precious Material And Weight:
0.105 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0