NSN 5935-01-376-1976

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-376-1976

Thread Class:
2a and 2b
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
1.312 inches
Overall Height:
0.656 inches
Overall Width:
0.556 inches
Environmental Protection:
Corrosion resistant
Distance Between Mounting Facility Centers:
1.000 inches
Threaded Device Type:
Coupling facility and mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
9 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Shell Type:
Solid
Connector Locking Method:
Jackscrew-socket
Thread Size:
0.164 inches and 0.138 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic melamine mineral filled single mating end

NSN 5935-01-376-1976

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum
Shell Surface Treatment:
Anodize
Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
9 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Jackscrew type-female and location-right handandjackscrew type-male and location-left hand
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.009 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0