# NSN 5935-01-376-2956

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-376-2956

#### **Body Style:**

Straight shape, internal coupling

#### **Overall Length:**

1.671 inches

## **Overall Diameter:**

1.281 inches

#### Mating End Quantity:

1

## **Contact Position Arrangement Style:**

15-35 single mating end

## **Contact Removability:**

Removable single mating end single contact grouping

# **Polarization Method:**

Key, multiple key groove

# Insert Position In Deg:

 $26.0 \ \text{and} \ 100.0 \ \text{and} \ 128.0 \ \text{and} \ 228.0 \ \text{and} \ 265.0$ 

#### Shell Type:

Solid

## **Connector Locking Method:**

Bayonet slot

## **Terminal Location:**

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping

#### **Insert Material:**

Plastic single mating end

## **Terminal Type:**

Crimp single mating end single contact grouping

#### **Shell Material:**

Aluminum alloy

#### Shell Surface Treatment:

Cadmium

## Included Contact Quantity:

37 single mating end single contact grouping

## Included Contact Type:

Round pin single mating end single contact grouping

## **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.037 gold grains, troy

# NSN 5935-01-376-2956

Electrical Plug Connector - Page 2 of 2



Precious Material:

Gold

# Test Data Document:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

96906-ms27467 government standard

Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A039b0 Mil-std (military Standard):

Mil-c-38999 spec.