## NSN 5935-01-376-4478

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-376-4478

Body Style: Straight type Overall Length: 2.850 inches Overall Height: 0.745 inches Overall Width: 0.250 inches Unthreaded Mounting Hole Diameter: 0.120 inches Distance Between Mounting Facility Centers: 2.600 inches Mating End Quantity: 1 Contact Position Arrangement Style: 23 single mating end Contact Removability: Nonremovable single mating end 2nd contact grouping Contact Maximum Current Rating In Amps:
Overall Length:  2.850 inches  Overall Height:  0.745 inches  Overall Width:  0.250 inches  Unthreaded Mounting Hole Diameter:  0.120 inches  Distance Between Mounting Facility Centers:  2.600 inches  Mating End Quantity:  1  Contact Position Arrangement Style:  23 single mating end  Contact Removability:  Nonremovable single mating end 2nd contact grouping  Contact Maximum Current Rating In Amps:
2.850 inches  Overall Height: 0.745 inches  Overall Width: 0.250 inches  Unthreaded Mounting Hole Diameter: 0.120 inches  Distance Between Mounting Facility Centers: 2.600 inches  Mating End Quantity: 1  Contact Position Arrangement Style: 23 single mating end  Contact Removability: Nonremovable single mating end 2nd contact grouping  Contact Maximum Current Rating In Amps:
Overall Height:  0.745 inches  Overall Width:  0.250 inches  Unthreaded Mounting Hole Diameter:  0.120 inches  Distance Between Mounting Facility Centers:  2.600 inches  Mating End Quantity:  1  Contact Position Arrangement Style:  23 single mating end  Contact Removability:  Nonremovable single mating end 2nd contact grouping  Contact Maximum Current Rating In Amps:
0.745 inches  Overall Width: 0.250 inches  Unthreaded Mounting Hole Diameter: 0.120 inches  Distance Between Mounting Facility Centers: 2.600 inches  Mating End Quantity: 1  Contact Position Arrangement Style: 23 single mating end  Contact Removability: Nonremovable single mating end 2nd contact grouping  Contact Maximum Current Rating In Amps:
Overall Width:  0.250 inches  Unthreaded Mounting Hole Diameter:  0.120 inches  Distance Between Mounting Facility Centers:  2.600 inches  Mating End Quantity:  1  Contact Position Arrangement Style:  23 single mating end  Contact Removability:  Nonremovable single mating end 2nd contact grouping  Contact Maximum Current Rating In Amps:
0.250 inches Unthreaded Mounting Hole Diameter: 0.120 inches Distance Between Mounting Facility Centers: 2.600 inches Mating End Quantity: 1 Contact Position Arrangement Style: 23 single mating end Contact Removability: Nonremovable single mating end 2nd contact grouping Contact Maximum Current Rating In Amps:
Unthreaded Mounting Hole Diameter:  0.120 inches  Distance Between Mounting Facility Centers:  2.600 inches  Mating End Quantity:  1  Contact Position Arrangement Style:  23 single mating end  Contact Removability:  Nonremovable single mating end 2nd contact grouping  Contact Maximum Current Rating In Amps:
0.120 inches  Distance Between Mounting Facility Centers: 2.600 inches  Mating End Quantity: 1  Contact Position Arrangement Style: 23 single mating end  Contact Removability: Nonremovable single mating end 2nd contact grouping  Contact Maximum Current Rating In Amps:
Distance Between Mounting Facility Centers:  2.600 inches  Mating End Quantity:  1  Contact Position Arrangement Style:  23 single mating end  Contact Removability:  Nonremovable single mating end 2nd contact grouping  Contact Maximum Current Rating In Amps:
2.600 inches  Mating End Quantity:  1  Contact Position Arrangement Style: 23 single mating end  Contact Removability:  Nonremovable single mating end 2nd contact grouping  Contact Maximum Current Rating In Amps:
Mating End Quantity:  1  Contact Position Arrangement Style: 23 single mating end  Contact Removability:  Nonremovable single mating end 2nd contact grouping  Contact Maximum Current Rating In Amps:
Contact Position Arrangement Style: 23 single mating end Contact Removability: Nonremovable single mating end 2nd contact grouping Contact Maximum Current Rating In Amps:
Contact Position Arrangement Style: 23 single mating end Contact Removability: Nonremovable single mating end 2nd contact grouping Contact Maximum Current Rating In Amps:
23 single mating end  Contact Removability:  Nonremovable single mating end 2nd contact grouping  Contact Maximum Current Rating In Amps:
Contact Removability:  Nonremovable single mating end 2nd contact grouping  Contact Maximum Current Rating In Amps:
Nonremovable single mating end 2nd contact grouping  Contact Maximum Current Rating In Amps:
Contact Maximum Current Rating In Amps:
F. O gingle mating and 2nd contact grouping
5.0 single mating end 2nd contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Friction
Terminal Location:
Back single mating end 2nd contact grouping
Contact Material:
Copper alloy single mating end 2nd contact grouping
Contact Surface Treatment:
Gold single mating end 2nd contact grouping
Insert Material:
Plastic polyphenylene single mating end and glass single mating end
Terminal Type:
Solder well single mating end 2nd contact grouping
Guide Design And Location:
D shape pin left-hand at 12 oclock and d shape socket right-hand at 12 oclock
D shape pin left-hand at 12 oclock and d shape socket right-hand at 12 oclock <b>Included Contact Quantity:</b>
Included Contact Quantity:
Included Contact Quantity: 20 single mating end 2nd contact grouping

Contact surfaces gold

## NSN 5935-01-376-4478

Electrical Receptacle Connector - Page 2 of 2



Precious	Material	And	Weight:
----------	----------	-----	---------

0.020 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0