

View Online at <https://aerobasegroup.com/nsn/5935-01-376-4480>

Body Style:

Straight type

Overall Length:

2.850 inches

Overall Height:

0.745 inches

Overall Width:

0.375 inches

Environmental Protection:

Heat resistant and cold resistant and salt water resistant and vibration resistant and shock resistant

Unthreaded Mounting Hole Diameter:

0.120 inches

Distance Between Mounting Facility Centers:

2.600 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

23 single mating end

Contact Removability:

Nonremovable single mating end 2nd contact grouping

Contact Maximum Current Rating In Amps:

75.0 single mating end 2nd contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Friction

Terminal Location:

Side single mating end 2nd contact grouping

Contact Material:

Copper alloy single mating end 2nd contact grouping

Contact Surface Treatment:

Gold single mating end 2nd contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end 2nd contact grouping

Terminal Type:

Pin single mating end 2nd contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end 2nd contact grouping

Insert Material Specification:

Mil-m-14g military specification single material response single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

20 single mating end 2nd contact grouping

Included Contact Type:

Round socket single mating end 2nd contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.020 gold grains, troy

Precious Material:

Gold

Supplementary Features:

Mounting method - unthreaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.