# NSN 5935-01-376-4481

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-376-4481

**Body Style:** 

Straight shape, external coupling

**Overall Length:** 

1.039 inches

**Overall Height:** 

Between 1.011 inches and 1.051 inches

**Overall Width:** 

Between 1.011 inches and 1.051 inches

#### **Environmental Protection:**

Moisture proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant and humidity resistant and oil resistant and shock resistant and thermal shock resistant and vibration resistant

#### **Unthreaded Mounting Hole Diameter:**

Between 0.123 inches and 0.138 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Height:

0.812 inches

### Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.812 inches

### **Distance From Mounting Shoulder To Front Face:**

0.812 inches

#### **Mating End Quantity:**

1

#### **Contact Position Arrangement Style:**

Afdx 11-5 single mating end

# Contact Removability:

Removable single mating end single contact grouping

# **Polarization Method:**

Keyway or multiple keyway

### **Insert Position In Deg:**

0.0

#### Shell Type:

Solid

# **Connector Locking Method:**

Bayonet pin

### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

# **Insert Material:**

Plastic epoxy single mating end

# **Contact Surface Treatment Specification:**

Mil-m-45204 military specification single treatment response single mating end single contact grouping

# NSN 5935-01-376-4481

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
Included Contact Quantity:
5 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Supplementary Features:
Mounting method - unthreaded hole
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-45204 spec.