NSN 5935-01-376-4944

Body Style: Straight type

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-376-4944

| Overall Length: |
|--|
| 2.850 inches |
| Overall Height: |
| 0.560 inches |
| Overall Width: |
| 0.375 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.100 inches |
| Distance Between Mounting Facility Centers: |
| 2.600 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 23 single mating end |
| Polarization Method: |
| 2 polarization posts |
| Connector Locking Method: |
| Friction |
| Terminal Location: |
| Back single mating end all contact groupings |
| Contact Material: |
| Copper alloy single mating end all contact groupings |
| Contact Surface Treatment: |
| Gold single mating end all contact groupings |
| Insert Material: |
| Plastic diallyl phthalate glass filled single mating end |
| Contact Surface Treatment Specification: |
| Mil-g-45204 military specification 1st treatment response single mating end all contact groupings |
| Terminal Type: |
| Crimp single mating end all contact groupings |
| Guide Design And Location: |
| D shape pin left-hand at 3 oclock and d shape socket right-hand at 3 oclock |
| Included Contact Quantity: |
| 3 single mating end 1st contact grouping20 single mating end 2nd contact grouping |
| Included Contact Type: |
| Coaxial pin single mating end 1st contact groupinground pin single mating end 2nd contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.035 gold grains, troy |
| |

NSN 5935-01-376-4944

Electrical Receptacle Connector - Page 2 of 2



| Precious Material: |
|-----------------------------------|
| Gold |
| Supplementary Features: |
| Mounting method - unthreaded hole |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| Mil-std (military Standard): |

Mil-g-45204 spec.