NSN 5935-01-376-7598

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-376-7598 **Thread Class:** 2b and 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** Between 1.040 inches and 1.060 inches **Overall Height:** 0.705 inches **Overall Width:** 0.250 inches **Distance Between Mounting Facility Centers:** 0.850 inches **Threaded Device Type:** Coupling facility and mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Jackscrew **Connector Locking Method:** Jackscrew-socket Thready Qty Per Inch (tpi): 56 Thread Size: 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end **Terminal Type:**

Solder well single mating end single contact grouping

Unable To Decode:

Unable to decode and unable to decode

NSN 5935-01-376-7598

Fiig: A039b0

Electrical Receptacle Connector - Page 2 of 2



| Included Contact Quantity: |
|--|
| 14 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Special Features: |
| Jackscrew type-male and location-right hand bottomandjackscrew type-female and location-left hand bottom |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.014 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |