NSN 5935-01-377-0772

Body Style:

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-377-0772

Straight type
Overall Length:
4.350 inches
Overall Height:
1.090 inches
Overall Width:
0.250 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
4.100 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Friction
Operating Tempurature Rating:
Between -55.0 degrees celsius and 125.0 degrees celsius
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic polyphenylene single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Wire wrap single mating end single contact grouping
Contact Material Specification:
Astm b196/187 assn standard single material response single mating end single contact grouping or qq-b-626 federal specification single

Insert Material Specification:

Mil-m-24519 military specification single material response single mating end

material response single mating end single contact grouping

NSN 5935-01-377-0772

Electrical Receptacle Connector - Page 2 of 2



Unable To Decode: Unable to decode and unable to decode **Included Contact Quantity:** 70 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.070 gold grains, troy **Precious Material:** Gold Shelf Life: N/a **Unit Of Measure:** Demilitarization: No Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.