Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-377-0785

#### **Body Style:**

Straight edge type w/mounting flange

#### **Overall Length:**

3.191 inches

### **Overall Height:**

0.692 inches

### **Overall Width:**

0.340 inches

#### **Environmental Protection:**

Shock resistant and vibration resistant and humidity resistant

### **Unthreaded Mounting Hole Diameter:**

#### 0.128 inches

**Distance Between Mounting Facility Centers:** 

2.937 inches

### **Board Accommodated Length:**

2.504 inches single board

#### **Board Accommodated Width:**

Between 0.054 inches and 0.071 inches

### Mating End Quantity:

1

### **Contact Position Arrangement Style:**

2 rows of independent contacts inserted board single mating end

### **Contact Removability:**

Nonremovable single mating end single contact grouping

### **Operating Tempurature Rating:**

Between -65.0 degrees celsius and 125.0 degrees celsius

### **Terminal Location:**

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

### **Insert Material:**

Plastic single mating end

## **Terminal Type:**

Tab, solder lug single mating end single contact grouping

## Included Contact Quantity:

30 single mating end single contact grouping

## Included Contact Type:

Bifurcated spring single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces gold



### **Precious Material And Weight:**

0.030 gold grains, troy

## **Precious Material:**

Gold

Shelf Life:

N/a

### Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A039b0