## NSN 5935-01-377-1083

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-377-1083 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight type **Overall Length:** 1.485 inches **Overall Height:** 0.618 inches **Overall Width:** 0.417 inches **Environmental Protection:** Vibration resistant and shock resistant and moisture resistant **Unthreaded Mounting Hole Diameter:** 0.096 inches **Distance Between Mounting Facility Centers:** 1.185 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 37 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Polarization Method:** Jackscrew **Shell Type:** Solid **Connector Locking Method:** Post jacksocket **Thread Size:** 0.086 inches **Terminal Location:** 

Side single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

## NSN 5935-01-377-1083

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, ty ii, grade c class i military specification single treatment response single mating end single contact grouping
Terminal Type:
Pin single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-a-200/8 federal specification single treatment response
Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
37 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Jackscrew type-female and location-right handandjackscrew type-female and location-left hand
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.037 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
<b></b>
Demilitarization:
No
Fiig:
A039b0

Mil-g-45204 spec.

Mil-std (military Standard):