NSN 5935-01-377-3535

Electrical Receptacle Connector - Page 1 of 2



Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
Between 4.300 inches and 4.330 inches
Overall Height:
Between 1.140 inches and 1.170 inches
Overall Width:
Between 4.300 inches and 4.330 inches
Environmental Protection:
Humidity resistant and shock resistant and thermal shock resistant and corrosion resistant and vibration resistant
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.558 inches and 0.566 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 3.870 inches and 3.880 inches
Distance From Mounting Shoulder To Front Face:
0.622 inches
Threaded Device Type:
Mounting hole
Mating End Quantity:
1
Contact Position Arrangement Style:
185 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Operating Tempurature Rating:
Between -65.0 degrees celsius and 200.0 degrees celsius
Thread Size:
0.138 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:

Gold single mating end single contact grouping

NSN 5935-01-377-3535

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic single mating end
Contact Surface Treatment Specification:
$Mil-g-45204, type \ 2, grade \ c, cl \ 1 \ military \ specification \ single \ treatment \ response \ single \ mating \ end \ single \ contact \ grouping$
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Nickel
Shell Surface Treatment Specification:
Mil-c-26074, grade a, cl 3 or 4 military specification single treatment response
Shell Material Specification:
Qq-a-591 federal specification single material response
Included Contact Quantity:
185 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.185 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.