

View Online at <https://aerobasegroup.com/nsn/5935-01-377-3535>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape

Overall Length:

Between 4.300 inches and 4.330 inches

Overall Height:

Between 1.140 inches and 1.170 inches

Overall Width:

Between 4.300 inches and 4.330 inches

Environmental Protection:

Humidity resistant and shock resistant and thermal shock resistant and corrosion resistant and vibration resistant

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.558 inches and 0.566 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 3.870 inches and 3.880 inches

Distance From Mounting Shoulder To Front Face:

0.622 inches

Threaded Device Type:

Mounting hole

Mating End Quantity:

1

Contact Position Arrangement Style:

185 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Operating Temperature Rating:

Between -65.0 degrees celsius and 200.0 degrees celsius

Thread Size:

0.138 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, cl 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Mil-c-26074, grade a, cl 3 or 4 military specification single treatment response

Shell Material Specification:

Qq-a-591 federal specification single material response

Included Contact Quantity:

185 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.185 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.