NSN 5935-01-377-7618

Tip Jack - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-01-377-7618

lentification Code Color: ed ody Style: erminal mounted erminal Length: 125 inches istance Between Mounting Facility Centers: 400 inches aximum Voltage Rating In Volts: 200.0 ac ccommodated Finger Type: est prod single finger	
ody Style: erminal mounted erminal Length: 125 inches istance Between Mounting Facility Centers: 400 inches aximum Voltage Rating In Volts: 200.0 ac ccommodated Finger Type:	
erminal mounted erminal Length: 125 inches istance Between Mounting Facility Centers: 400 inches aximum Voltage Rating In Volts: 200.0 ac ccommodated Finger Type:	
erminal Length: 125 inches istance Between Mounting Facility Centers: 400 inches aximum Voltage Rating In Volts: 200.0 ac ccommodated Finger Type:	
125 inches istance Between Mounting Facility Centers: 400 inches aximum Voltage Rating In Volts: 200.0 ac ccommodated Finger Type:	
istance Between Mounting Facility Centers: 400 inches aximum Voltage Rating In Volts: 200.0 ac ccommodated Finger Type:	
400 inches aximum Voltage Rating In Volts: 200.0 ac ccommodated Finger Type:	
aximum Voltage Rating In Volts: 200.0 ac ccommodated Finger Type:	
200.0 ac ccommodated Finger Type:	
ccommodated Finger Type:	
est prod single finger	
inger Accommodation Diameter:	
080 inches single finger	
inger Accommodation Length:	
250 inches single finger	
ounting Leg Length:	
125 inches	
apacitance In Picofarads:	
5	
ounting Facility Type And Quantity:	
terminal	
erminal Type:	
ab, solder lug	
recious Material And Location:	
ontact and terminal surfaces gold	
recious Material:	
old	
urface Treatment:	
old terminal	
urface Treatment:	
old terminal	
helf Life:	
/a	
nit Of Measure:	
emilitarization:	
0	
iig:	
03400	