## NSN 5935-01-378-7620

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-378-7620

Thread Class:
2b and 2a
Thread Direction:
Right-hand
Body Style:
Angle shape, pcb type
Overall Length:
3.450 inches
Overall Height:
0.635 inches
Overall Width:
0.640 inches
Unthreaded Mounting Hole Diameter:
0.250 inches
Distance Between Mounting Facility Centers:
3.200 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
4 rows of contacts non-inserted board single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Thread Size:
0.086 inches
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping or gold single mating end single contact
grouping and copper single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end
Terminal Type:
Printed circuit single mating end single contact grouping

Unable To Decode:
Unable to decode and unable to decode

## NSN 5935-01-378-7620

Fiig: A039b0

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
122 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Jackscrew type-male and location-right handandjackscrew type-female and location-left hand
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.122 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No