

View Online at <https://aerobasegroup.com/nsn/5935-01-378-7784>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape w/cable clamp

Overall Length:

1.540 inches

Bushing Diameter:

0.625 inches

Overall Height:

1.000 inches

Overall Width:

1.000 inches

Unthreaded Mounting Hole Diameter:

Between 0.124 inches and 0.129 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.718 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.718 inches

Distance From Mounting Shoulder To Front Face:

0.780 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

N single mating end

Contact Removability:

Removable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Connector Cable Strain Relief Method:

Shrinkable tubing

Thready Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic fluorinated ethylene propylene single mating end or plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.