Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-378-9152

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape threaded |
| Overall Length: |
| Between 0.835 inches and 0.865 inches |
| Overall Diameter: |
| 1.468 inches |
| Distance From Mounting Shoulder To Front Face: |
| 0.378 inches |
| |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 Contract Descition American contract Otales |
| Contact Position Arrangement Style: |
| 4 single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 35.0 single mating end single contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 2000.0 single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 0.0 |
| Shell Type: |
| Solid |
| Thread Length: |
| 0.378 inches |
| Thready Qty Per Inch (tpi): |
| 18 |
| Thread Size: |
| 0.250 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and nickel single mating end single contact grouping |
| Insert Material: |
| Plastic diallyl phthalate single mating end |



Terminal Type:

Turret single mating end single contact grouping

Shell Material:

Aluminum

Shell Surface Treatment:

Cadmium

Included Contact Quantity:

4 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.004 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-81511 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Double stub

Specification Data:

81349-mil-c-55181 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0