# NSN 5935-01-379-5033

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-379-5033

**Body Style:** 

Straight shape, external coupling

**Overall Length:** 

1.805 inches

**Overall Height:** 

Between 0.928 inches and 0.949 inches

Overall Width:

Between 0.928 inches and 0.949 inches

#### **Environmental Protection:**

Moisture proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant and humidity resistant and oil resistant and shock resistant and thermal shock resistant and vibration resistant

#### **Unthreaded Mounting Hole Diameter:**

0.120 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Height:

0.719 inches

#### Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.719 inches

## **Distance From Mounting Shoulder To Front Face:**

Between 0.855 inches and 0.860 inches

**Mating End Quantity:** 

1

#### **Contact Position Arrangement Style:**

Oct-98 single mating end

#### **Contact Removability:**

Removable single mating end single contact grouping

Shell Type:

Solid

#### **Connector Locking Method:**

Bayonet pin

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

#### **Insert Material:**

Plastic polyamide single mating end

# **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

#### **Terminal Type:**

Crimp single mating end single contact grouping

#### **Shell Material:**

Aluminum alloy 6061

# NSN 5935-01-379-5033

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:	
Nickel	
Shell Material Specification:	
Ams 4150 assn standard single material response	
Included Contact Quantity:	
6 single mating end single contact grouping	
Included Contact Type:	
Round socket single mating end single contact grouping	
Precious Material And Location:	
Contact surfaces gold	
Precious Material And Weight:	
0.030 gold grains, troy	
Precious Material:	
Gold	
Shelf Life:	
N/a	
Unit Of Measure:	
<del>.</del>	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Standard):	
Mil-g-45204 spec.	