Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-379-5492

Thread Class:	
2a	
Thread Direction:	
Right-hand	
Body Style:	
Straight shape, external coupling	
Overall Length:	
1.937 inches	
Overall Height:	
Between 1.969 inches and 2.031 inches	
Overall Width:	
Between 1.969 inches and 2.031 inches	
Unthreaded Mounting Hole Diameter:	
Between 0.142 inches and 0.157 inches	
Center To Center Distance Between Mounting Facilities Parallel To Height:	
1.562 inches	
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:	
1.562 inches	
Distance From Mounting Shoulder To Front Face:	
Between 0.812 inches and 0.843 inches	
Threaded Device Type:	
Coupling facility	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
28-21 single mating end	
Contact Removability:	
Removable single mating end single contact grouping	
Polarization Method:	
Keyway or multiple keyway	
Insert Position In Deg:	
250.0	
Shell Type:	
Solid	
Connector Locking Method:	
Externally threaded shell	
Thready Qty Per Inch (tpi):	
18	
Thread Size:	
1.750 inches	
Terminal Location:	
Back single mating end single contact grouping	

Electrical Receptacle Connector - Page 2 of 2



Contact Material: Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Rubber silicone class q single mating end **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum **Shell Surface Treatment:** Cadmium and chromate and nickel **Included Contact Quantity:** 37 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.037 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Uns Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-c-5015 spec.