## NSN 5935-01-380-1236

Plug Dummy Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-380-1236

**Body Style:** 

Straight shape, internal coupling w/backshell

**Overall Diameter:** 

1.183 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

14-5 single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

0.0

Solid

Shell Type:

\_

**Connector Locking Method:** 

Bayonet slot

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:** 

Plastic single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204, type 2, grade c, cl, 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

**Shell Material:** 

Aluminum alloy 6061 or aluminum alloy 380.0 or aluminum alloy a380.0

**Shell Surface Treatment:** 

Cadmium and chromate

**Shell Surface Treatment Specification:** 

Qq-p-416, type 2, cl 3 federal specification all treatment responses

**Shell Material Specification:** 

Qq-a-367, type 6 federal specification 1st material response or qq-a-591 federal specification 2nd material response or qq-a-591 federal specification 3rd material response

**Included Contact Quantity:** 

5 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.030 gold grains, troy

## NSN 5935-01-380-1236

Plug Dummy Connector - Page 2 of 2



Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.